

LUMUL

Flex Strip


PREMIUM

5YR



COB 384 LED

EPISTAR™ COB



MODEL NO	FP-COB-384-8	LEDs / m	384
INPUT VOLTAGE	DC 24V	SMD	COB
VOLTAGE TYPE	CONSTANT VOLTAGE	LED SPACING	2.6MM
POWER PER M	8W	LED PLACEMENT	SINGLE
BEAM ANGLE	180°	CUTTING UNIT	83.33MM
BEAM DIRECTION	TOP VIEW	WORKING HOURS	50000 HOURS
CRI (RA)	>90	WORKING TEMPERATURE	-25° TO 45°C
3000K	720 LM	FPC WIDTH	8MM
4000K	880 LM	FPC THICKNESS	2OZ
6000K	960 LM	FPC TYPE	STRAIGHT
MAX LUMEN EFFICIENCY	120 LM/W	MAX LENGTH	8M (1 FEED) 16M (2 FEEDS)
COLOURS	2700K, 3000K, 3200K, 3500K, 4000K, 5000K, 6000K, 6500K	IP OPTIONS	IP20, IP67
		WARRANTY	5 YEARS

The LUMUL COB flexible strips are available in 384, 480 and 512 led/m configurations. All models are available in IP20 and in an IP67 clear silicone sleeve. 8mm FPC strips are also available in an IP67 neon sleeve (diffused).