

LUMUL

Flex Strip

PREMIUM

5 YR



COB 480 LED

EPISTAR™ COB



MODEL NO	FP-COB-480-8		LEDs / m	480
INPUT VOLTAGE	DC 24V		SMD	COB
VOLTAGE TYPE	CONSTANT VOLTAGE		LED SPACING	2.08MM
POWER PER M	9W		LED PLACEMENT	SINGLE
BEAM ANGLE	180°		CUTTING UNIT	50MM
BEAM DIRECTION	TOP VIEW		WORKING HOURS	50000 HOURS
CRI (RA)	>90		WORKING TEMPERATURE	-25° TO 45°C
		NEON	FPC WIDTH	8MM
3000K	900 LM	675 LM	FPC THICKNESS	2OZ
4000K	990 LM	743 LM	FPC TYPE	STRAIGHT
6000K	1080 LM	810 LM	MAX LENGTH	8M (1 FEED)
MAX EFFICIENCY LM/W	120	90		16M (2 FEEDS)
COLOURS	2700K, 3000K, 3200K, 3500K, 4000K, 5000K, 6000K, 6500K		IP OPTIONS	IP20, IP67
			WARRANTY	5 YEARS

The LUMUL COB flexible strips are available in 384, 480 and 512 led/m configurations. All models are available in IP20 and in an IP67 clear silicone sleeve. 8mm FPC strips are also available in an IP67 neon sleeve (diffused).