

LUMUL

Flex Strip

PREMIUM



2835 60 LEDs CURRENT REGULATOR LONG RUN



MODEL NO	FPB-2835-60-LRA	LEDs / m	60
INPUT VOLTAGE	DC 24V	SMD	2835
VOLTAGE TYPE	CONSTANT VOLTAGE	LED SPACING	16.67MM
POWER PER M	5.04W	LED PLACEMENT	SINGLE
MAX CURRENT / LED	TBC	CUTTING UNIT	100MM
BEAM ANGLE	120°	L70 (70% OF ORIGINAL BRIGHTNESS)	54000 HOURS
BEAM DIRECTION	TOP VIEW	WORKING TEMPERATURE	-25° TO 60°C
CRI (Ra)	80+	FPC WIDTH	10MM
WAVELENGTH / TEMPERATURE	2800K-9500K	FPC THICKNESS	3OZ
BRIGHTNESS	2800-3200K	423 LM/M	MAX LENGTH
	4000-4500K	431 LM/M	
	5000-5500K	438 LM/M	42M (2 FEEDS)
	6500-7000K	438 LM/M	IP OPTIONS
	8000-9500K	448 LM/M	
MAX LUMEN EFFICIENCY	89 LM/W	WARRANTY	5 YEARS (OPTIONAL 2 YRS)

Available in this series:

- 60 & 120 LEDs per meter
- Low, medium & high wattage & brightness